

# DH-IPC-HFW2231T-ZS-S2

2MP Lite IR Vari-focal Bullet Network Camera



- 2MP, 1/2.8" CMOS image sensor, low illuminance, high image definition
- Outputs 2MP (1920 × 1080)@25/30 fps
- H.265 codec, high compression rate, ultra-low bit rate
- Built-in IR LED, max IR distance: 60 m
- ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments
- Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes
- Intelligent detection: Intrusion, tripwire
- Abnormality detection: Motion detection, video tampering, no SD card, SD card full, SD card error, network disconnected, IP conflict, illegal access, voltage detection
- Supports max. 256 GB Micro SD card
- 12V DC/PoE power supply
- IP67 protection ,IK10 protection (optional)



## Series Overview

With upgraded H.265 encoding technology, Dahua Lite series network camera has efficient video encoding capacity, which saves bandwidth and storage space. This camera adopts the latest starlight technology and displays better color image in the condition of low illumination. It supports SD card storage, dust-proof function, waterproof function and vandal-proof function, complying with the standards of IP67 and IK10 (Supported by some select models).

## Functions

### Smart H.265+ & Smart H.264+

With advanced scene-adaptive rate control algorithm, Dahua smart encoding technology realizes the higher encoding efficiency than H.265 and H.264, provides high-quality video, and reduces the cost of storage and transmission.

### WDR

With advanced Wide Dynamic Range (WDR) technology, Dahua network camera provides clear details in the environment of strong brightness contrast. The bright and dark area can get clear video even in high brightness environment or with backlight shadow.

### Starlight

With advanced image processing technology and optical technology, Dahua Starlight technology can provide clear colorful video in the environment of low illuminance. It widely applies to various environments of low illuminance.

### IVS

With advanced video algorithm, Dahua IVS technology supports intelligent functions, such as tripwire and intrusion.

### Cyber Security

Dahua network camera is equipped with a series of key security technologies, such as security authentication and authorization, access control, trusted protection, encrypted transmission, and encrypted storage, which improve its security defense and data protection, and prevent malicious programs from invading the device.

### Protection (IP67, wide voltage)

**IP67:** The camera passes a series of strict test on dust and soak. It has dust-proof function, and the enclosure can works normal after soaking in 1 m deep water for 30 minutes.

**Wide voltage:** The camera allows ±30% (for some power supplies) input voltage tolerance (wide voltage range), and it is widely applied to outdoor environment with instable voltage.

Technical Specification

|                            |                                                   |
|----------------------------|---------------------------------------------------|
| Camera                     |                                                   |
| Image Sensor               | 1/2.8" 2Megapixel progressive CMOS                |
| Max. Resolution            | 1920 (H) × 1080 (V)                               |
| ROM                        | 128 MB                                            |
| RAM                        | 128 MB                                            |
| Scanning System            | Progressive                                       |
| Electronic Shutter Speed   | Auto/Manual 1/3 s–1/100000 s                      |
| Min. Illumination          | 0.002 Lux@F1.5                                    |
| S/N Ratio                  | >56 dB                                            |
| Illumination Distance      | 60 m (196.85 ft)                                  |
| Illuminator On/Off Control | Auto/Manual                                       |
| Illuminator Number         | 4 (IR LED)                                        |
| Pan/Tilt/Rotation Range    | Pan: 0°–360°<br>Tilt: 0°–90°<br>Rotation: 0°–360° |

| Lens                 |      |                                                                 |                       |                      |                      |
|----------------------|------|-----------------------------------------------------------------|-----------------------|----------------------|----------------------|
| Lens Type            |      | Motorized vari-focal                                            |                       |                      |                      |
| Mount Type           |      | φ14                                                             |                       |                      |                      |
| Focal Length         |      | 2.7 mm–13.5 mm                                                  |                       |                      |                      |
| Max. Aperture        |      | F1.5                                                            |                       |                      |                      |
| Field of View        |      | Horizontal: 109°–28°<br>Vertical: 57°–16°<br>Diagonal: 131°–33° |                       |                      |                      |
| Iris Type            |      | Fixed                                                           |                       |                      |                      |
| Close Focus Distance |      | 0.8 m–0.8 m (2.62 ft–2.62 ft)                                   |                       |                      |                      |
| DORI Distance        | Lens | Detect                                                          | Observe               | Recognize            | Identify             |
|                      | W    | 44.1 m<br>(144.69 ft)                                           | 17.6 m<br>(57.74 ft)  | 8.8 m<br>(28.87 ft)  | 4.4 m<br>(14.44 ft)  |
|                      | T    | 151.7 m<br>(497.70 ft)                                          | 60.6 m<br>(198.82 ft) | 30.3 m<br>(99.41 ft) | 15.1 m<br>(49.65 ft) |

|             |                     |
|-------------|---------------------|
| Smart Event |                     |
| IVS         | Tripwire; intrusion |

|                   |                                                                                                                                 |
|-------------------|---------------------------------------------------------------------------------------------------------------------------------|
| Video             |                                                                                                                                 |
| Video Compression | H.265; H.264; H.264B; MJPEG (only supported by the sub stream)                                                                  |
| Smart Codec       | Smart H.265+/ Smart H.264+                                                                                                      |
| Video Frame Rate  | Main stream:<br>1920 × 1080 (1 fps-25/30 fps)<br>Sub stream:<br>704 × 576 (1 fps-25 fps)<br>704 × 480 (1 fps-30 fps)            |
| Stream Capability | 2 streams                                                                                                                       |
| Resolution        | 1080p (1920 × 1080); 1.3M (1280 × 960); 720p (1280 × 720); D1 (704 × 576/704 × 480); VGA (640 × 480); CIF (352 × 288/352 × 240) |

|                         |                                                                       |
|-------------------------|-----------------------------------------------------------------------|
| Bit Rate Control        | CBR/VBR                                                               |
| Video Bit Rate          | H.264: 32 kbps–6144 kbps<br>H.265: 12 kbps–6144 kbps                  |
| Day/Night               | Auto(ICR)/Color/B/W                                                   |
| BLC                     | Yes                                                                   |
| HLC                     | Yes                                                                   |
| WDR                     | 120 dB                                                                |
| White Balance           | Auto/natural/street lamp/outdoor/manual/regional custom               |
| Gain Control            | Auto/Manual                                                           |
| Noise Reduction         | 3D NR                                                                 |
| Motion Detection        | OFF/ON (4 areas, rectangular)                                         |
| Region of Interest(Rol) | Yes (4 areas)                                                         |
| Smart Illumination      | Yes                                                                   |
| Image Rotation          | 0°/90°/180°/270° (Supports 90°/270° with 1080p resolution and lower.) |
| Mirror                  | Yes                                                                   |
| Privacy Masking         | 4 areas                                                               |

|             |                                                                                                                                                                                          |
|-------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Alarm       |                                                                                                                                                                                          |
| Alarm Event | No SD card; SD card full; SD card error; network disconnection; IP conflict; motion detection; video tampering; tripwire; intrusion; illegal access; voltage detection; safety exception |

|                     |                                                                                                                                                                                                                                                           |
|---------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Network             |                                                                                                                                                                                                                                                           |
| Network             | RJ-45 (10/100 Base-T)                                                                                                                                                                                                                                     |
| SDK and API         | Yes                                                                                                                                                                                                                                                       |
| Cyber Security      | Video encryption; firmware encryption; configuration encryption; Digest; WSSE; account lockout; security logs; IP/MAC filtering; generation and importing of X.509 certification; syslog; HTTPS; 802.1x; trusted boot; trusted execution; trusted upgrade |
| Protocol            | IPv4; IPv6; HTTP; TCP; UDP; ARP; RTP ; RTSP; RTCP; RTMP; SMTP; FTP; SFTP; DHCP; DNS; DDNS; QoS; UPnP; NTP; Multicast; ICMP; IGMP; NFS; PPPoE; Bonjour                                                                                                     |
| Interoperability    | ONVIF (Profile S/Profile G/Profile T); CGI; P2P; Milestone; Genetec                                                                                                                                                                                       |
| User/Host           | 20                                                                                                                                                                                                                                                        |
| Storage             | FTP; Micro SD card (support max. 256 G); NAS; SFTP                                                                                                                                                                                                        |
| Browser             | IE<br>Chrome<br>Firefox                                                                                                                                                                                                                                   |
| Management Software | Smart PSS; DSS; DMSS                                                                                                                                                                                                                                      |
| Mobile Phone        | IOS; Android                                                                                                                                                                                                                                              |

|                |                                                                                                                                                                        |
|----------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Certification  |                                                                                                                                                                        |
| Certifications | CE-LVD: EN62368-1<br>CE-EMC: Electromagnetic Compatibility Directive 2014/30/EU<br>FCC: 47 CFR FCC Part 15, Subpart B<br>UL/CUL: UL60950-1 CAN/CSA C22.2 No.60950-1-07 |

## Power

|                   |                      |
|-------------------|----------------------|
| Power Supply      | 12V DC/PoE (802.3af) |
| Power Consumption | < 9.6W               |

## Environment

|                      |                                                     |
|----------------------|-----------------------------------------------------|
| Operating Conditions | -30°C to +60°C (-22°F to +140°F)/less than ≤ 95% RH |
| Storage Temperature  | -40°C to +60°C (-40°F to +140°F)                    |
| Protection           | IP67;IK10(optional)                                 |

## Structure

|              |                                      |
|--------------|--------------------------------------|
| Casing       | Metal                                |
| Dimensions   | 244.1 mm × Φ90.4 mm (9.61" × Φ3.26") |
| Net Weight   | 0.86 kg (1.90 lb)                    |
| Gross Weight | 1.10 kg (2.43 lb)                    |

## Ordering Information

| Type                   | Part Number            | Description                                        |
|------------------------|------------------------|----------------------------------------------------|
| 2MP Camera             | DH-IPC-HFW2231TP-ZS-S2 | 2MP Lite IR Vari-focal Bullet Network Camera,PAL   |
|                        | DH-IPC-HFW2231TN-ZS-S2 | 2MP Lite IR Vari-focal Bullet Network Camera,NTSC  |
| Accessories (optional) | PFA130-E               | Junction Box                                       |
|                        | PFA152-E               | Pole Mount                                         |
|                        | PFM321D                | DC12V1A Power Adapter                              |
|                        | LR1002-1ET/1EC         | Single-port Long Reach Ethernet over Coax Extender |
|                        | PFM900-E               | Integrated Mount Tester                            |
|                        | PFM114                 | TLC SD Card                                        |

## Accessories

### Optional:



PFA130-E  
Junction Box



PFA152-E  
Pole Mount



PFM321D  
DC12V1A Power  
Adapter




LR1002-1ET/1EC  
Single-port Long  
Reach Ethernet over  
Coax Extende



PFM900-E  
Integrated Mount  
Tester



PFM114  
TLC SD Card



## Dimensions (mm[inch])

